



# GPL 12750

## 12V 75.0Ah

GPL 12750 is a general purpose battery with 10 years expected life under normal float charge. As with all CSB batteries, all are rechargeable, highly efficient, leak proof and maintenance free.




### Specification

Cells Per Unit	6
Voltage Per Unit	12
Capacity	75Ah @ 20hr-rate to 1.75V per cell @25 °C (77°F)
Weight	Approx. 26.7kg(58.7 lbs)
Maximum Discharge Current	800A (5sec)
Internal Resistance	Approx. 4.5mΩ
Operating Temperature Range	Discharge: -20°C~50°C (-4°F~122°F) Charge: -20°C~50°C (-4°F~122°F) Storage: -20°C~40°C (-4°F~104°F)
Nominal Operating Temperature Range	25°C±3°C (77°F±5°F)
Float Charging Voltage	13.5 to 13.8 VDC/Unit Average at 25°C (77°F)
Recommended Maximum Charging Current Limit	22.5A
Equalization and Cycle Service	14.4 to 15.0 VDC/unit Average at 25°C (77°F)
Self Discharge	CSB Batteries can be stored for more than 6 months at 25°C (77°F). Please charge batteries before using. For higher temperatures the time interval will be shorter.
Terminal	Thread Insert & Bolt
Container Material	-Polypropylene (UL94-HB)*Flammability resistance of UL94-V0 can be available upon request.



CSB-manufactured batteries are UL-recognized components under UL924 and UL1989. CSB is also certified by ISO 9001 and ISO 14001.

### Dimensions



### Constant Current Discharge Characteristics Unit:A (25°C , 77°F)


F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	325.00	215.00	158.00	93.30	53.40	31.00	21.50	16.70	14.40	9.36	7.85	4.45
1.67V	297.00	197.50	152.40	90.99	52.56	30.51	21.15	16.56	14.26	9.30	7.69	4.42
1.70V	285.00	190.00	150.00	90.00	52.20	30.30	21.00	16.50	14.20	9.28	7.62	4.41
1.75V	252.50	175.00	144.00	85.40	50.70	29.80	20.60	16.20	13.95	9.11	7.56	4.33
1.80V	220.00	160.00	138.00	80.80	49.20	29.30	20.20	15.90	13.70	8.93	7.50	4.24
1.83V	187.50	145.00	132.00	76.20	47.70	28.80	19.80	15.60	13.45	8.76	7.44	4.16

### Constant Power Discharge Characteristics Unit:W (25°C , 77°F)


F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	3,420.00	2,370.00	1,720.00	1,070.00	623.00	363.00	253.00	197.00	170.00	112.00	94.70	53.20
1.67V	3,175.00	2,181.00	1,664.00	1,042.00	617.00	359.50	249.50	196.30	169.50	111.30	94.49	52.92
1.70V	3,070.00	2,100.00	1,640.00	1,030.00	611.00	358.00	248.00	196.00	169.00	111.00	94.40	52.80
1.75V	2,760.00	1,935.00	1,585.00	983.00	595.50	352.50	244.00	192.50	166.00	109.00	92.65	51.90
1.80V	2,450.00	1,770.00	1,530.00	936.00	580.00	347.00	240.00	189.00	163.00	107.00	90.90	51.00
1.83V	2,140.00	1,605.00	1,475.00	889.00	564.50	341.50	236.00	185.50	160.00	105.00	89.15	50.10

● All mentioned values are average values.


### Trickle (or Float) Service Life




### Capacity Retention Characteristic




### Battery Voltage and Charge Time for Standby Use



### Terminal Voltage (V) and Discharge Time (25°C 77°F)



### Battery Voltage and Charge Time for Cycle Use



### Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/Cell	1.75	1.70	1.55	1.30
Discharge Current (A)	0.2C>(A)	0.2C<(A)<0.5C	0.5C<(A)<1.0C	(A)>1.0C

### Charging Procedures

Application	Charge Voltage (V/Cell)			Max. Charge Current
	Temperature	Set Point	Allowable Range	
Cycle Use	25°C (77°F)	2.45	2.40-2.50	0.3C
Standby	25°C (77°F)	2.275	2.25-2.30	

Sales Office URL: [WWW.CSB-BATTERY.COM](http://WWW.CSB-BATTERY.COM)

**CSB BATTERY CO., LTD.**  
TAIWAN OFFICE  
Tel: +886-2-8751-5000  
Fax: +886-2-8751-6161  
E-mail: [service@csb-battery.com.tw](mailto:service@csb-battery.com.tw)

**CSB BATTERY LOGISTICS (SHANGHAI) CO., LTD.**  
SHANGHAI OFFICE  
Tel: +86-21-5046-1622, 5046-0833  
Fax: +86-21-5064-3314

**CSB BATTERY TECHNOLOGIES, INC**  
USA OFFICE  
Tel: +1-817-244-7777/1-8003 CSBUSA(272872)  
Fax: +1-817-244-4445  
E-mail: [csb@csb-battery.com](mailto:csb@csb-battery.com)

**CSB BATTERY LOGISTICS (SHANGHAI) CO., LTD.**  
BEIJING OFFICE  
Tel: +86-10-6597-8060, 6597-8070  
Fax: +86-10-6597-8050  
E-mail: [chinasis@csb-battery.com](mailto:chinasis@csb-battery.com)

**CSB BATTERY OF NETHERLANDS B.V**  
NETHERLANDS OFFICE  
Tel: +31(0) 180 418 140  
Fax: +31(0) 180 418 327  
E-mail: [eurossales@csb-battery.com](mailto:eurossales@csb-battery.com)

**CSB BATTERY LOGISTICS (SHANGHAI) CO., LTD.**  
SHENZHEN OFFICE  
Tel: +86-755-2694-2788/2606/2706  
Fax: +86-755-2694-2748  
E-mail: [she@csb-battery.com](mailto:she@csb-battery.com)